



Oil separator class I (EN858) with integrated sludge part (Vol. 3000 l).
 Inlet and Outlet sewer D160. Max. flow rate: 10 l/s

ACCESSORY: ACD Automatic closure device DN160

h = Separator connection height from ground
 h = _____ mm (Max. 2500 mm)

16	NOT INCLUDING: Base plate (4950x1800, s=150 mm) concrete K30-2, steel reinforcement A500HW T8 #200		
15	ACCESSORY: Anchoring belt (Polyester), 4 pcs (x)	<input type="checkbox"/>	
14	ACCESSORY: Heating cable set for maintenance shaft (230V). 2 pcs (x) Effective 150 W. MCMK cable for electricity (230V) connection length 5 m. Including insulation inner cover. Not including frost insulation	<input type="checkbox"/>	
13	ACCESSORY: Data Transfer Unit	<input type="checkbox"/>	(x)
12	ACCESSORY: ACD Automatic closure device DN160 for oil density less than 0.90 g/cm³	<input type="checkbox"/>	(x)
11	ACCESSORY: Ladder in EuroHUK 600 maintenance shaft, material Al	<input type="checkbox"/>	(x)
10	ACCESSORY: Floating adjustable cover ø600, Standard EN124 (2 pcs) Cover class A15 (1.5 tn) (x) Cover class C250 (25 tn) Cover class D400 (40 tn) Frame	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
9	EuroHUK 600 maintenance shaft (as needed), material PE-MD EuroHUK 600 h 9-13 (x) EuroHUK 600 h13-17 EuroHUK 600 h17-21 EuroHUK 600 h21-25	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	h= 900...1300 mm h=1300...1700 mm h=1700...2100 mm h=2100...2500 mm
8	PP-HUK 600 maintenance shaft (as needed), material PP plastic PP-HUK 600 h 9-13 (x) PP-HUK 600 h13-17 PP-HUK 600 h17-21 PP-HUK 600 h21-25	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	h= 900...1300 mm h=1300...1700 mm h=1700...2100 mm h=2100...2500 mm
7	Ventilation outlet	PVC/PE	D110
6	Alarm unit (as needed) STANDARD ALARM: Oil alarm unit (x) SPECIAL ALARM: Oil/Sludge alarm unit	<input type="checkbox"/> <input type="checkbox"/>	
5	Coalescator		
4	Outlet sewer	PVC	D160
3	Inlet sewer	PVC	D160
2	Wall	GRP	D1400
1	Material: Glass Reinforced Plastic (GRP) pH 3-10/Heat endurance continued 60°C (temporary max. 80°C)		ø1400, L=4950 mm
A	Storage volume of sludge		3 000 l
B	Effective volume		3 100 l
C	Oil storage volume		350 l

NOT INCLUDING: Base plate

This drawing and the technical information included in the drawing are property of Wavin-Labko. All the national regulations concerning this product have to be checked before purchase of the product. Installation have to be done according to installation manual.

Title: EuroPEK Roo NS10/3000 Oil separator, Class I (EN858) Drawing type: CUSTOMER DRAWING

Design by: AL/JS Approved by: HT 16.08.2018 Drawing no.: 38CB03ae Date: 15.08.2018 Scale:

Construction site:

WAVIN-LABKO Ltd. VISIOKATU 1 FIN-33720 TAMPERE FINLAND tel. +358 20 1285200 fax. +358 20 1285280