


EuroREK NS4 SL (EN1825)  
grease separator (indoor installation,  
on the floor)

Max. flow rate 4 l/s

C	Grease storage capacity		160 l	
B	Effective capacity		900 l	
A	Sludge capacity		400 l	
11	ACCESSORY: Washing nozzle (x)			<input type="checkbox"/>
10	ACCESSORY: Labcom data transfer unit (x)			<input type="checkbox"/>
9	ACCESSORY: Imubox quick coupling box (x)			<input type="checkbox"/>
8	ACCESSORY: Emptying pipe with flange (DN80) (x)			<input type="checkbox"/>
7	Sampling valve			1
6	Grease alarm unit			1
5	Lockable gas tight cover	PE-MD	D400	1
4	Ventilation outlet	PVC	D110	1
3	Outlet sewer	PE	D110	1
2	Inlet sewer	PVC	D110	1
1	Tank (pH3-10/Heat endurance max. 50°C)	PE-MD	2070x750x1670 mm	1

Product EuroREK NS4 SL grease separator (indoor)			Drawing type CUSTOMER DRAWING	
Design by AL/TL	Approved by HT 08.07.2016	Drawing no. 32F B03be	Date 07.07.2016	Scale (A4) 1:25
 WAVIN-LABKO OY Visiokatu 1 FIN-33720 Tampere FINLAND puh. +358 020 1285 200 fax. +358 0201285 280			Construction site	

This drawing and the technical information included in the drawing are property of Wavin-Labko Ltd. Authorities' regulations must be known before providing the product. Products must be installed according to installation instructions.

