

h =Vattengång inlopp till färdig mark (Max. 2500 mm)


h = _____ mm

Max. flöde: 4 l/s

Dimensionering: Enligt EN 1825
Förlängningshalsar: PP-HUK D600

14	Lagringsvolym slam		405 l	
13	Lagringsvolym fett		285 l	
12	Effektiv volym		960 l	
11	EXTRA UTRUSTNING: Gjutjärnsbetäckning \varnothing 600 (2 st)			
	Lock A15 (1.5 tn) + ram (x) <input type="checkbox"/>			
	Lock C250 (25 tn) + ram <input type="checkbox"/>			
	Lock D400 (40 tn) + ram <input type="checkbox"/>		Art. nr: 8533022	
10	EXTRA UTRUSTNING: PP-HUK Förhöjningshals, material: PP (\varnothing 602/670) h =Vattengång inlopp till färdig mark (Max. 2500 mm)			(2)
	PP-HUK 600 h 9-13 (x) <input type="checkbox"/>		h = 900...1300 mm	
	PP-HUK 600 h13-17 <input type="checkbox"/>		h =1300...1700 mm	
	PP-HUK 600 h17-21 <input type="checkbox"/>		h =1700...2100 mm	
	PP-HUK 600 h21-25 <input type="checkbox"/>		h =2100...2500 mm	
9	EXTRA UTRUSTNING: LABCOM kommunikationsenhet (x) <input type="checkbox"/>			
8	EXTRA UTRUSTNING: Nivåalarm SET-2000 med SET DM/3 och SET/OS2 givare (x) <input type="checkbox"/>			
7	Ventilation utlopp	PVC	D110	1
6	Utlopp	PVC	D110	1
5	Inlopp	PVC	D110	1
4	Krage för PP-HUK 600	GAP	D600	2
3	Mellanvägg	GAP	D1000	1
2	Inloppsskärm	GAP		1
1	Material: GAP "Lasa Komposit", pH 3-10/max temp 80°C		\varnothing 1000 L=3000 mm	1

OBS! SPECIAL MODEL (2x PP-HUK 600 Förhöjningshals)

Produkt namn: EuroFAM NS4 fettavskiljare med slamdel		Ritning typ: KUNDRITNING	
Designerad av: MG/JS	Godkänd av: JP 16.11.07	Arbetsnummer: 32ED23_r	Datum: 16.11.2007
Projekt:		Skala:	
		 Wavin Sweden Kjulamon 6 SE-63506 ESKILSTUNA www.wavin.se wavin.se@wavin.com +46 (0) 16 - 541 0000	

This drawing and the technical information included in the drawing are property of Wavin Finland. All the national regulations concerning this product have to be checked before purchase of the product. Installation have to be done according to installation manual.