



Number	49150/03	Replaces	49150/02
Issued	17/09/2019	Scope	AR 200
Contract number	Q95/001	Page	1-3

Product Certificate

## Electrofusion fittings and tapping tees

Based on pre-certification tests as well as periodic inspections by Kiwa Nederland B.V., the products referred to in this certificate and marked with the GASTEC QA mark, supplied by

### Georg Fischer Wavin A.G.

may, on delivery, be relied upon to comply with the GASTEC QA approval requirements 200, for "Electrofusion fittings and saddles made from Polyethylene (PE)" dated May 2019.

Ronald Karel  
Kiwa

This certificate is issued by Kiwa Nederland B.V. in conjunction with the KIWA regulations for Certification 2017.

This certificate consists of 3 pages.  
Publication of the certificate is allowed.

Kiwa Nederland B.V.  
Sir. Winston Churchillaan 273  
P.O. Box 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel.+31 88 998 4400  
info@kiwa.nl  
www.kiwa.nl

**supplier**  
Georg Fischer Wavin A.G.  
Industriestrasse 24  
4553 Subingen  
Switzerland

www.gfps.com

T +41 32 613 21 11  
F +41 52 614 31 74



Number	49150/03	Replaces	49150/02
Issued	17/09/2019	Scope	AR 200
Contract number	Q95/001	Page	2-3

## Electrofusion fittings and tapping tees

---

### PRODUCT SPECIFICATION

#### **Elgef plus (+GF+) PE-100 Electrofusion couplers**

Straight coupler PE 100 for use in:

PE-80 and PE 100 pipes, SDR 11 and 17,6, (use of enclosed plastic support sleeves in SDR 17.6 pipe required) diameters 20, 25, 32 and 40 mm.

PE-80 and PE 100 pipes, SDR 11 and 17,6, diameters 50 and 63, 75, 90, 110, 125, 140, 160, 180, 200 and 225 mm.

Max. working pressure for PE 100 pipes: 8 bar

Max. working pressure for PE 80 pipes: 4 bar

Material code: E1 or H10

#### **EZYLINE PE-100 Electrofusion couplers type LI**

Straight coupler for use in:

PE 80 and PE-100 pipes, SDR 11 diameters: 32, 40, 50 and 63 mm.

PE 80 and PE-100 pipes, SDR 11 and SDR17,6 diameters: 75, 90 and 110 mm.

Max. working pressure for PE 100 pipes: 8 bar.

Max. working pressure for PE 80 pipes: 4 bar.

Material code: E1 or H10

#### **EZYLINE PE-100 Electrofusion couplers type LI**

Straight coupler for use in:

PE 80 and PE-100 pipes, SDR 11 and SDR17,6 diameters: 125, 160, 180, 200 and 225 mm.

Max. working pressure for PE 100 pipes: 8 bar.

Max. working pressure for PE 80 pipes: 4 bar.

Material code: E1 or H10.

#### **MONOLINE PE-100 Electrofusion couplers type LU**

Straight Electrofusion couplers, for use in:

PE 80 and PE-100 pipes, SDR 11 and SDR 17,6, diameters 125, 140, 160, 180, 200 and 225 mm.

Max. working pressure for PE 100 pipes: 8 bar.

Max. working pressure for PE 80 pipes: 4 bar.

Material code: E1 or H10.

#### **MONOLINE PE-100 Electrofusion couplers type LU**

Straight Electrofusion couplers, for use in:

PE 80 and PE-100 pipes, SDR 11 diameters 20, 25, 32, 40, 50 and 63 mm.

PE 80 and PE-100 pipes, SDR 11 and SDR 17,6, diameters 75, 90 and 110 mm.

Max. working pressure for PE 100 pipes: 8 bar.

Max. working pressure for PE 80 pipes: 4 bar.

Material code: E1 or H10.

Number	49150/03	Replaces	49150/02
Issued	17/09/2019	Scope	AR 200
Contract number	Q95/001	Page	3-3

## Electrofusion fittings and tapping tees

### ELGEF Plus (+GF+) PE-100 saddles

Saddles for use in PE-100 and PE-80 pipes, SDR 11 and SDR 17,6, in the following sizes:

#### No. 53 131 400: 360 ° swivel saddle with outlet in the dimensions:

63 x 20, 63 x 25, 63 x 32, 63 x 40, 63 x 50, 63 x 63, 75 x 20, 75 x 25, 75 x 32, 75 x 40, 75 x 50, 75 x 63, 90 x 20, 90 x 25, 90 x 32, 90 x 40, 90 x 50, 90 x 63, 110 x 20, 110 x 25, 110 x 32, 110 x 40, 110 x 50, 110 x 63, 125 x 20, 125 x 25, 125 x 32, 125 x 40, 125 x 50, 125 x 63, 140 x 20, 140 x 25, 140 x 32, 140 x 40, 140 x 50, 140 x 63, 160 x 20, 160 x 25, 160 x 32, 160 x 40, 160 x 50, 160 x 63, 180 x 20, 180 x 25, 180 x 32, 180 x 40, 180 x 50, 180 x 63, 200 x 20, 200 x 25, 200 x 32, 200 x 40, 200 x 50, 200 x 63, 225 x 20, 225 x 25, 225 x 32, 225 x 40, 225 x 50, 225 x 63 mm.

#### No. 53 131 000: Saddle with Electrofusion outlet 63 mm in the following sizes:

63 x 63, 75 x 63, 90 x 63, 110 x 63, 125 x 63, 140 x 63, 160 x 63, 180 x 63, 200 x 63 and 225 x 63 mm.

#### No. 53 130 000: Service saddle with Electrofusion outlet 63 mm inclusive blind piece in the following sizes:

63 x 63, 75 x 63, 90 x 63, 110 x 63, 125 x 63, 140 x 63, 160 x 63, 180 x 63, 200 x 63 and 225 x 63 mm.

#### No. 53 131 400: Saddle Monobloc in the following sizes:

40 x 20, 40 x 25, 40 x 32, 50 x 20, 50 x 25, 50 x 32, 63 x 20, 63 x 25, 63 x 32 mm.

Material code: E1 or H10.

### APPLICATION AND USE

Electro fusion fittings and saddles made of polyethylene (PE) intended for use in plastic piping systems for the supply of gaseous fuels of the 2nd and 3rd family according to EN 437 with a maximum operating pressure of 10 bar and an operating temperature of 20°C as reference temperature.

### MARKING

- GASTEC QA or GASTEC QA logo or punch mark.
- Number of system standard: EN 1555
- Name and or trademark of manufacturer: Georg Fischer Wavin A.G.
- Nominal outside diameter(s) of pipe, Dn:
- Material and designation
- Design application series
- Applicable SDR fusion range of pipe:
- Manufacturers information (production period (year and month in figures or code), name or code for the production site if produced at different sites)
- Intended use: GAS

### RECOMMENDATIONS FOR END USERS

Check at the time of delivery whether:

- the producer has delivery in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport.

Consult the producer's processing guidelines for the proper storage and transport methods.

Check whether this certificate is still valid by consulting Kiwa Nederland B.V. or the Kiwa website.

If you should reject a product on the basis of the above, please contact the supplier and, if necessary, Kiwa Nederland B.V.