

Pipe Dimensions

Clay pipe weights and dimensions

March 2020

Hepworth
Fired to Perfection

CLAY

Range	Plain ended (P/E), Fitted Coupling (C) or Socketed (S)	Nominal Inner Diameter (mm)	Outer Diameter(mm)	Length (mm)	Weight (kg)
SuperSleve	P/E	100	122	1600	14.9
	P/E	150	178	1750	30.7
	P/E	225	263	1750	59.5
	C	225	263	1750	60.3
	P/E	300	358	2000	145.1
	C	300	358	2000	146.3
SuperSleve Rocker pipes	P/E	150	178	300	4.6
	P/E	150	178	600	9.2
	P/E	150	178	1000	15.4
	P/E	225	263	300	10.2
	C	225	263	300	11
	P/E	225	263	600	20.4
	C	225	263	600	21.2
	P/E	225	263	1000	34
	C	225	263	1000	34.8
	P/E	300	358	300	21.8
	C	300	358	300	23
	P/E	300	358	600	43.6
	C	300	358	600	44.8
	P/E	300	358	1000	72.5
C	300	358	1000	73.7	
HepLine	P/E	100	122	1600	14.9
	P/E	150	178	1750	30.7
	C	225	263	1750	59.5
	C	300	358	2000	145.1
Unjointed	S	100	130	1000	13.7
	S	150	192	1000	25.4
	S	225	271	1000	60
	S	300	372	1000	85

For any further information, please call our Technical Advisory Service on 0844 856 5165.