

Declaration of Performance N° Regulation (EU) 305/2011		
Unique identification code of the	5Z344G	
product-type		
Identification of the product	OsmaW Rubber Reducer GY 40x32. Material Hardness	
(Type, batch or serial number)	and Type: 50-WA & WC	
Intended use		
	Elastomeric seal for pipe joints used in water and	
	drainage applications.	
Contact	Wavin	
	Registered Office	
	Crow Edge	
	Sheffield	
	S36 4HG	
ACVP system	System 4	
TO 1 1 TO C 1 1 1	' 1 . 1 1DC ENIZO4 4 400Z E1 . ' C 1	

Declared Performances based on harmonized standard BS EN 681-1: 1996. Elastomeric Seals - Material requirements for pipe joint seals used in water and drainage applications. KM07729 (BSI).

Essential characteristics	Performance	hEN
Dimensional Tolerance	Pass	
Release of Dangerous Substances	n/a	
Durability	Conforms to specification in table 2	BS EN 681-1: 1996
Tightness (gas and liquid)	Conforms to specification in table 2	

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

date of issue	name and function	Allyan
7 th August 2013	Andrew Ryall Technical Manager	



Declaration of Performance N° Regulation (EU) 305/2011		
Unique identification code of the	2Z347G	
product-type		
Identification of the product	OsmaW Rubber Reducer GY 50x32. Material Hardness	
(Type, batch or serial number)	and Type: 50-WA & WC	
Intended use		
	Elastomeric seal for pipe joints used in water and	
	drainage applications.	
Contact	Wavin	
	Registered Office	
	Crow Edge	
	Sheffield	
	S36 4HG	
ACVP system	System 4	
TO 1 1 TO C 1 1 1	. 1 . 1 1D0 EN (04 4 4007 El	

Declared Performances based on harmonized standard BS EN 681-1: 1996. Elastomeric Seals - Material requirements for pipe joint seals used in water and drainage applications. KM07729 (BSI).

Essential characteristics	Performance	hEN
Dimensional Tolerance	Pass	
Release of Dangerous Substances	n/a	
Durability	Conforms to specification in table 2	BS EN 681-1: 1996
Tightness (gas and liquid)	Conforms to specification in table 2	

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

date of issue	name and function	Allyan
7 th August 2013	Andrew Ryall Technical Manager	



Declaration of Performance N° Regulation (EU) 305/2011		
Unique identification code of the	2Z349G	
product-type		
Identification of the product	OsmaW Rubber Reducer GY 50x40. Material Hardness	
(Type, batch or serial number)	and Type: 50-WA & WC	
Intended use		
	Elastomeric seal for pipe joints used in water and	
	drainage applications.	
Contact	Wavin	
	Registered Office	
	Crow Edge	
	Sheffield	
	S36 4HG	
ACVP system	System 4	
•		

Declared Performances based on harmonized standard BS EN 681-1: 1996. Elastomeric Seals - Material requirements for pipe joint seals used in water and drainage applications. KM07729 (BSI).

Essential characteristics	Performance	hEN
Dimensional Tolerance	Pass	
Release of Dangerous Substances	n/a	
Durability	Conforms to specification in table 2	BS EN 681-1: 1996
Tightness (gas and liquid)	Conforms to specification in table 2	

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

date of issue	name and function	Allyan
7 th August 2013	Andrew Ryall Technical Manager	