

Protect Against Odour. Protect Your Health.

 $\operatorname{Hep}_{\vee} O^{\mathsf{TM}}$ is a unique self-sealing waste valve that permanently prevents the escape of foul sewer air into the living space. This noxious gas may contain viruses and bacteria which are harmful to our health and wellbeing.

As a dry sealing valve, $\operatorname{Hep}_{v}O^{TM}$ utilises a purpose designed membrane that opens under the water pressure and closes to form a tight seal after the water has discharged under normal atmospheric conditions.

Unlike a p-trap, it retains its seal even if the fixture is infrequently or never used.












Range

The Hep O™ valve and installation adaptors are available in 32mm (11/4") and 40mm (11/2") sizes.

Applications

Hep O™ is a secure alternative for a traditional waste trap. It can be installed vertically or horizontally for convenience and spacesaving opportunities.





No odours even in warm climates or where plumbing fixtures are not frequently used



Also great for recreational vehicles - caravans, boats, travel buses, trains, etc

Quality requirements

Hep,O™ is manufactured under a quality management system which is approved to ISO 9001 and ISO 14001.

It is kitemarked to ATS 5200-047:2005 (KM 618560). It also has International Certification including a Watermark License (Australia), Listing to ASME / ANSI A112.18.8 (USA) and CSA Attestation (Canada).

Based on external test results, Hep, O™ valve has a life expectancy at least equivalent to current water sealed traps.

System benefits

Permanent odour prevention

Self-sealing valve prevents foul and unhealthy sewer gas which can carry viral pathogens into the living space.

Resistance to back pressure

Provides protection against sewer gas back pressure up to 10 times the level possible with a trap system.

- **O Not influenced by solid or greasy waste materials** Can be used in all residential and commercial applications.
- Higher flow rate of discharge water Faster drainage of fixtures.
- Space saving

Allows for vertical or horizontal installation, achieving significant and valuable space-saving opportunities.

- No air admittance valves required The venting of the waste system for negative pressure conditions is no longer necessary.
- Not affected by syphonage Hep O™ retains seal performance and allows the placement of a greater number of appliances together on fewer discharge pipes.
- **D** Low Noise

Hep, O™ operates quietly and is not subject to "gurgling" noises.

Installation Video Guide





Wavin is part of Orbia, a community of companies working together

WAVIN ASIA PACIFIC E-mail wavinapac@wavin.com | Internet www.wavin.com/asia









